

MCBs 1P - 10kA



P1 MB 1P...

Order code	Characteristic	In	Icn	Qty per pkg	Wt
	Curve	[A]	[kA]	n°	[kg]
Thermomagnetic circuit breakers - 1P - characteristic B.					
P1 MB 1P B01	B	1	10	12	0.115
P1 MB 1P B02	B	2	10	12	0.115
P1 MB 1P B04	B	4	10	12	0.115
P1 MB 1P B06	B	6	10	12	0.115
P1 MB 1P B10	B	10	10	12	0.115
P1 MB 1P B16	B	16	10	12	0.115
P1 MB 1P B20	B	20	10	12	0.115
P1 MB 1P B25	B	25	10	12	0.115
P1 MB 1P B32	B	32	10	12	0.115
P1 MB 1P B40	B	40	10	12	0.115
P1 MB 1P B50	B	50	10	12	0.115
P1 MB 1P B63	B	63	10	12	0.115
Thermomagnetic circuit breakers - 1P - characteristic C.					
P1 MB 1P C01	C	1	10	12	0.115
P1 MB 1P C02	C	2	10	12	0.115
P1 MB 1P C04	C	4	10	12	0.115
P1 MB 1P C06	C	6	10	12	0.115
P1 MB 1P C10	C	10	10	12	0.115
P1 MB 1P C16	C	16	10	12	0.115
P1 MB 1P C20	C	20	10	12	0.115
P1 MB 1P C25	C	25	10	12	0.115
P1 MB 1P C32	C	32	10	12	0.115
P1 MB 1P C40	C	40	10	12	0.115
P1 MB 1P C50	C	50	10	12	0.115
P1 MB 1P C63	C	63	10	12	0.115
Thermomagnetic circuit breakers - 1P - characteristic D.					
P1 MB 1P D01	D	1	10	12	0.115
P1 MB 1P D02	D	2	10	12	0.115
P1 MB 1P D04	D	4	10	12	0.115
P1 MB 1P D06	D	6	10	12	0.115
P1 MB 1P D10	D	10	10	12	0.115
P1 MB 1P D16	D	16	10	12	0.115
P1 MB 1P D20	D	20	10	12	0.115
P1 MB 1P D25	D	25	10	12	0.115
P1 MB 1P D32	D	32	10	12	0.115
P1 MB 1P D40	D	40	10	12	0.115
P1 MB 1P D50	D	50	10	12	0.115
P1 MB 1P D63	D	63	10	12	0.115

General characteristics

- Ratings 1 to 63A
- Pole width 18mm
- Positive indication with flag window
- Tripping characteristics B, C and D
- Mounting on 35mm DIN rail (IEC/EN 60715)
- Add-on blocks available.

Operational characteristics

- Rated insulation voltage U_i : 440V
- Rated impulse withstand voltage U_{imp} : 4kV
- Rated operating voltage U_e : 230/400VAC.

Certifications and compliance

Certifications obtained: TUV and UL Recognized for USA and Canada (cURus - File E359585) as Protectors-Components; products having this type of marking are intended for use components of complete workshop-assembled equipment.
Compliant with standards: IEC/EN 60898-1, IEC/EN 60947-2, UL 1077, CSA C22.2 n°235.

MCBs 1P+N - 6kA



P1 MB 1N...

Order code	Characteristic	In	Icn	Qty per pkg	Wt
	Curve	[A]	[kA]	n°	[kg]
Thermomagnetic circuit breakers - 1P+N - characteristic C.					
P1 MB 1N C01	C	1	6	6	0.190
P1 MB 1N C02	C	2	6	6	0.190
P1 MB 1N C04	C	4	6	6	0.190
P1 MB 1N C06	C	6	6	6	0.190
P1 MB 1N C10	C	10	6	6	0.190
P1 MB 1N C16	C	16	6	6	0.190
P1 MB 1N C20	C	20	6	6	0.190
P1 MB 1N C25	C	25	6	6	0.190
P1 MB 1N C32	C	32	6	6	0.190
P1 MB 1N C40	C	40	6	6	0.190
P1 MB 1N C50	C	50	6	6	0.190
P1 MB 1N C63	C	63	6	6	0.190

General characteristics

- Ratings 1 to 63A
- Pole width 18mm
- Positive indication with flag window
- Tripping characteristics C
- Mounting on 35mm DIN rail (IEC/EN 60715)
- Add-on blocks available.

Operational characteristics

- Rated insulation voltage U_i : 440V
- Rated impulse withstand voltage U_{imp} : 4kV
- Rated operating voltage U_e : 230/400VAC.

Certifications and compliance

Certifications obtained: TUV and UL Recognized for USA and Canada (cURus - File E359585) as Protectors-Components; products having this type of marking are intended for use components of complete workshop-assembled equipment.

Compliant with standards: IEC/EN 60898-1, IEC/EN 60947-2, UL 1077, CSA C22.2 n°235.